

## FLOOD TYPE COOLANT PUMPS



- Tank Capacity - 1 Gallon
- Coolant pump motor - 1/16 HP
- With 1/2" (13 mm) diameter neoprene hose
- 1/4" (6 mm) diameter flexible metal flush nozzle with flow control

▲ 5300-1001



- Tank Capacity - 2 Gallon
- Coolant pump motor - 1/8 HP
- With 1/2" (13 mm) diameter neoprene hose
- With metal flexible flush nozzle with flow control valve.
- 7 ft electrical cord and push button switch

▲ 5300-1002



▲ 5300-1326,1425

- Tank Capacity
  - 5300-1326 - 3.25 Gallon,
  - 5300-1425 - 4.25 Gallon,
- Coolant pump motor - 1/8 HP
- With neoprene hose
- With modular coolant hose
- With electrical cord and push button switch



▲ 5300-1005

- Tank Capacity - 5 Gallon
- Coolant pump motor - 1/8 HP
- Neoprene hose
- Metal flexible nozzle with flow control valve



▲ 5300-1010

- Tank Capacity - 10 Gallon
- Coolant pump motor - 1/8 HP
- With neoprene hose
- With metal flexible flush nozzle with control valve

## ALIGN VACUUM CLEANER

### AUTO-CORD REEL FUNCTION INCLUDED PACKAGE ACCESSORIES



**CE-2020**

**CE-2023**

- VOLTAGE: 110V-240V
- POWER CONSUMPTION: 1000/700W
- SUCTION EFFICIENCY: 180W
- MOTOR: 1 MOTOR 2 STAGE
- CAPACITY: 20/23 L
- STANDARD ACCESSORIES: ø32(B)
- G.W.: 8/9 KGS
- PACKING SIZE: 330x340x670mm



**AMT-10.0**

- VOLTAGE: 110V-240V
- POWER CONSUMPTION: 1000W
- SUCTION EFFICIENCY: 210W
- MOTOR: 1 MOTOR 2 STAGE
- CAPACITY: 40 L
- STANDARD ACCESSORIES: ø32(B)
- G.W.: 21 KGS
- PACKING SIZE: 405x405x730mm



**SPCE-1040**

**SPCE-1060**

- VOLTAGE: 110V-240V
- POWER CONSUMPTION: 2000W
- SUCTION EFFICIENCY: 300W
- MOTOR: 2 MOTOR 2 STAGE
- CAPACITY: 40/60 L
- STANDARD ACCESSORIES: ø32(B)
- G.W.: 25/27 KGS
- PACKING SIZE: 405x405x780/890mm